

US009638385B2

(12) United States Patent Shin et al.

(10) Patent No.: US 9,638,385 B2 (45) Date of Patent: May 2, 2017

(54) HEAD LAMP IN VEHICLE

(71) Applicants:**Hyundai Motor Company**, Seoul (KR); **Hyundai Mobis Co., Ltd.**, Seoul (KR)

(72) Inventors: Jik Soo Shin, Incheon (KR); Soohan Im, Seoul (KR)

(73) Assignees: **Hyundai Motor Company**, Seoul (KR); **Hyundai Mobis Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 184 days.

(21) Appl. No.: 14/521,994

(22) Filed: Oct. 23, 2014

(65) Prior Publication Data
US 2015/0184822 A1 Jul. 2, 2015

(30) Foreign Application Priority Data

Dec. 26, 2013 (KR) 10-2013-0164098

(51) Int. Cl. F21S 8/12 (2006.01) F21S 8/10 (2006.01)

(52) U.S. CI. CPC F21S 48/1784 (2013.01); F21S 48/125 (2013.01); F21S 48/13 (2013.01); F21S 48/142 (2013.01); F21S 48/145 (2013.01)

(58) Field of Classification Search

CPC .. F21S 48/125; F21S 48/1258; F21S 48/1305; F21S 48/14; F21S 48/142; F21S 48/145; B60Q 1/1438

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2002/0051365 A	11* 5/200	02 Yokoi	F21S 48/145
2011/0170308 A	A1* 7/20	11 Kinoshita	362/512 a B60Q 1/076
2013/0107560 A	M 5/20	13 Kimetal	362/516

FOREIGN PATENT DOCUMENTS

JP	2008-027650	A	2/2008
JP	2008-192313	Α	8/2008
KR	10-2004-0037949	Α	5/2004
KR	10-0506712	B1	8/2005
KR	10-2010-0025253	Α	3/2010
KR	10-2011-0074345	Α	6/2011
	0	Cor	tinued)

Primary Examiner — Bao Q Truong Assistant Examiner — Nathaniel Lee (74) Attorney, Agent, or Firm — Morgan, Lewis & Bockius LLP

(57) ABSTRACT

A head lamp in a vehicle may include a light source for emitting a light, a reflector for reflecting the light forward from the light source, a lens for transmitting the light being forwarded toward a front from the light source and the reflector, a holder having one end coupled to the lens and the other end coupled to the reflector to make the lens spaced at a predetermined distance from the reflector, and a movable shield disposed between the light source and the reflector and the lens for selectively shielding a portion of the light being forwarded toward the lens from the light source and the reflector, or not shielding the portion of the light being forwarded toward the lens from the light source and the reflector when being moved to create a space between the movable shield and a lower end of the holder to allow the light pass through.

11 Claims, 7 Drawing Sheets

